Casting frames and ramps

Zone 1

















Casting frame for casting into a recess

Casting frames are made from angle sections (L). The accompanying heavy duty corner brackets ensure accurate assembly. The frames have been designed to enable assembly with mitred corners. But they can also be supplied as straight sections in the desired lengths.

T-edging is usually used as a separator between two different mats in a single recess.

Ramp edging Ideal for mats that are approx. 10-12 mm or 16-20 mm high. The edging is made from aluminium and is used when mats are installed on top of a floor where there are not any recesses. It is attached from above using screws into drilled holes. Edging is supplied without pre-drilled holes, and without screws.



Material:	Aluminium.		
Temperature:	-40°C to +70°C		
Guarantee: 3 years against manufacturing defects.			

Dimensions	Internal dimensions	External dimensions + corner brackets	Article no.	
CASTING FRAMES				
20 x 10 (2) mm	8 mm	10 + 7 mm	100/10	
15 x 15 (1,5) mm	13,5 mm	15 + 7 mm	100/15	
20 x 20 (2) mm	18 mm	20 + 7 mm	100/20	
25 x 25 (3) mm	22 mm	25 + 6 mm	100/25	
RAMP EDGING				
50 / 67 mm	12 mm		100/12 RAMP	
50 / 67 mm	18 mm		100/18 RAMP	
T-EDGING				
30 x 17,2 (2,8) mm	16 mm		100/15T	
30 x 22,2 (2,8) mm	21 mm		100/20T	

